



CONSTRUCTION MATERIALS

TECHNOLOGIES

LABORATORY TEST REPORT

Report for: Mbrico Tile Decks
P.O. Box 1108
Bettendorf, IA 52722

Attention: Nick McManus

Assembly:	Mbrico Tile	Manufacturer:	Mbrico Tile Decks
Project No.:	MBTD-001-02-02	Source:	Mbrico Tile Decks
Date Received:	Dec. 6, 2017	Date Tested:	Dec. 19, 2017

Purpose: Determine the simulated wind uplift pressure in accordance with the **ANSI/FM Approvals 4474 Appendix B: *Simulated Wind Uplift Pull Test Procedure.*** Testing was modified to determine the passing load of a single Mbrico Tile installed into the Mbrico T-Track joists.

Test Methods: Testing was completed as described in the ANSI/FM Approvals 4474 (2004) Appendix B: *Simulated Wind Uplift Pull Test Procedure.*

Sampling: The following materials were received by PRI.

<u>Product</u>	<u>Source</u>	<u>Date</u>
Mbrico Tiles	Moline, IL	Dec. 6, 2017
Mbrico T-Track	Moline, IL	Dec. 6, 2017

All other roofing components were procured by PRI through local distribution.

Conditioning: Specimens were conditioned at 74±4°F for less than 28 days prior to testing.

MBTD-001-02-02

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Results: Testing was performed at standard laboratory conditions. Test pressures were increased by 60 lbf increments and maintained at each interval for 1 minute. Raw test is provided in Appendix B.

Table 1. ANSI/FM 4474(B) & TAS 114(D) Results for Assembly No. 1

Component:	Attachment Detail	Passing Uplift Force (lbf)
Joists:	(2) Mbrico T-Track (6560-T6 extruded aluminum alloy joists; section drawing contained in Appendix A) were secured 23-11/16" o.c.	1,680
Tile:	(1) Mbrico Tile (23-11/16" x 23-11/16" x 3/4" porcelain tile bonded to a Mbrico proprietary composite backing with 1/16" tongue along two edges) was set into the joists by engaging the tongue into the T-Track grooves.	

Remarks: Assuming a tributary are of 4-ft² per tile, the resultant passing uplift load for the Mbrico Tile to the Mbrico T-Track is 420 psf.

Statement of Compliance:

The laboratory test results presented in this report are representative of the material supplied and test specimens constructed. Testing was conducted in accordance **ANSI/FM Approvals 4474 Appendix B: Simulated Wind Uplift Pull Test Procedure** with modifications noted herein.

Signed: 

 Zachary Priest, P.E.
 Director


Report Issue History:

Issue #	Date	Pages	Revision Description (if applicable)
Original	02/23/2018	4	NA

MBTD-001-02-02


The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Mbrico Tiles



Mbrico Joists

Mbrico T-Track



MBTD-001-02-02

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

Test Data for Assembly No. 1

Property	Specimen 1
Max Passing Load, (lbf)	1,680
Failing Load, (lbf)	On rise to 1,740
Failing Time, (sec)	0
Failure Mode	Adhesive failure of composite backing to tile
Max Passing Pressure, (psf)	420 ¹

Notes: 1) Pressure is calculated based on 4-ft² tributary area for each tile



END OF REPORT

MBTD-001-02-02

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.