

Product Data Sheet – Profi-Line adjustable pedestals

Product name	Art. no.	nominal construction height / adjustment range [mm]	deadweight tonnage * [kN]	PU
PRO S	946070	30 - 53	8,0	10
PRO M	946071	53 - 82	8,0	10
PRO L	946072	70 - 117	8,0	10
PRO XL	946079	74 - 168	8,0	10



individual parts	material
top	PP-C
threaded ring	PP-C
extension ring	PP-C
baseplate	PP-C

The height-adjustable support feet are suitable for predominantly static centric compressive loading in multiple-supported systems.

\* The specified value of the load capacity represents recommended values. Under these loads, the adjustable feet deform by only approx. 2 mm. The load-bearing capacity up to the actual breakage is many times higher.

Product Data Sheet – Profi-Line adjustable pedestals

Product name	Art. no.	height extension [mm]	deadweight tonnage * [kN]	PU
Extensions ring	946074	40	8,0	10
Extensions ring	946073	100	8,0	10



component	material
Extensions ring	PP-C

The height-adjustable support feet are suitable for predominantly static centric compressive loading in multiple-supported systems.

\* The specified value of the load capacity represents recommended values. Under these loads, the adjustable feet deform by only approx. 2 mm. The load-bearing capacity up to the actual breakage is many times higher.

© by E.u.r.o.Tec GmbH · Status 09/2018 · Changes, additions, typesetting and printing errors are reserved.

Product Data Sheet – Profi-Line adjustable pedestals

Product name	Art. no.	material	PU
L adapter	946075	PP-C	10
Click adapter 40	946076	PP-C	10
Click adapter 60	946077	PP-C	10
Stone adapter	946078	PP-C	10



L adapter



Click adapter 40



Click adapter 60



Stone adapter



adapter	materials
L-, Click-, Stone adapter	PP-C

The height-adjustable support feet are suitable for predominantly static centric compressive loading in multiple-supported systems.

\* The specified value of the load capacity represents recommended values. Under these loads, the adjustable feet deform by only approx. 2 mm. The load-bearing capacity up to the actual breakage is many times higher.

Observe the manufacturer's instructions for the support of the stone slabs! The use of our system does not release planners/processors from informing themselves about the manufacturer's specifications of other products (installed together with our system).

Product Data Sheet – Profi-Line adjustable pedestals

Product name	Art. no.	nominal construction height / adjustment range H [mm]	deadweight tonnage * [kN]	PU
PRO XS incl. L /Stone adapter	954061	22 - 30	8,0	20
PRO XXS incl. L /Stone adapter	954020	10 - 15	4,0	50
Extension plate XXS	954021	5	4,0	50



PRO XXS



Extension plate XXS



individual parts	material
top	PP-C
threaded ring	PP-C
extension ring	PP-C
baseplate	PP-C

The height-adjustable support feet are suitable for predominantly static centric compressive loading in multiple-supported systems.

Observe the manufacturer's instructions for the support of the stone slabs! The use of our system does not release planners/processors from informing themselves about the manufacturer's specifications of other products (installed together with our system).

If you are not familiar with the application of the product at hand, especially with the handling according to given regulations, it is essential to get in contact with our technical application support department.